

# ELITE MULTIVALVULAS 10W40



AUTOMOTIVE

Lubricants

## Description

Synthetic-based lubricant oil developed for use in modern petrol or diesel car engines. Its synthetic components provide it with high chemical stability and together with its extraordinary performance allow for longer oil change intervals. Due to its low viscosity, facilitates cold start-up, cares for hydraulic tappets and subsequently maintains perfect lubrication at any temperature. Its thermal stability also means that it takes longer than a conventional oil under normal conditions of use.

## Properties

- Engine tests obtained in the approval tests of the different manufacturers ensure engine cleanliness and resistance to oil oxidation, enabling maximum engine performance throughout the period of lubricant use.
- Its low viscosity in cold facilitates start-up and the smooth operation of the hydraulic tappet systems.
- Optimum fuel consumption due to its viscometric characteristics, and specific additivation to reduce friction.
- Minimum lubricant consumption, lower than other products of a similar viscosity, as its composition includes low volatility synthetic base oils.

## Quality Levels

- VW 502.00/505.00
- ACEA A3/B4
- API SN/CF
- MB 229.3
- RN0700/RN0710

## Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			10W40
Density at 15 °C	g/mL	ASTM D 4052	0.858
Viscosity at 100 °C	cSt	ASTM D 445	15.0
Viscosity at 40 °C	cSt	ASTM D 445	97
Viscosity at -25 °C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	150 min.
Flash point, open cup	°C	ASTM D 92	200 min.
Pour point	°C	ASTM D 97	-30
T.B.N.	mg KOH/g	ASTM D 2896	10
Sulphated ashes	% in weight	ASTM D 874	1.5
Bosch Injector Shearing: Viscosity at 100 °C after shearing	cSt	CEC L-14-93	12,5 min.
Noack Volatility, 1h a 250 °C	% in weight	CEC L-40-93	13 max.

A safety data file is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Review 6 December 2014.