

Description

Products from the DESMOLDOIL range are compounds formulated to act as mould-release agents in various applications. They contain a selected mix of oils, which include appropriate additives and have been treated to fulfil their function.

The range of DESMOLDOIL products has been carefully analysed to guarantee compliance with our customers' demands in relation to all kinds of applications and finishes (pieces of concrete, formwork, etc.) on any kind of surface, such as wood, iron, etc.

Properties

- Good oxidation resistance and storage stability.
- Excellent mould release properties.
- Environmentally friendly (can not be labelled).
- Exceptional coverage.
- Excellent finish.

Technical specifications

	UNIT	METHOD	90		
			L	P	
ASTM colour		ASTM D 1500	<1	0.5	0.5
Density at 15 °C	g/mL	ASTM D 4052	0.857	0.865	0.865
Viscosity at 40 °C	cSt	ASTM D 445	11.5	24	24
Viscosity at 100 °C	cSt	ASTM D 445	3.3	4.3	4.3
Pour point	°C	ASTM D 97	-9	-12	-12
Additives		-	No	No	Yes

Unless otherwise indicated, the values stated in the technical characteristics are not specifications and should only be considered as typical.

A safety data sheet is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 3. October 2013.