

EMPATEM CC-30 H

INDUSTRY



Lubricants

Description

A highly refined natural paraffin mineral oil with special additives, which provide the properties required in continuous steel casting work. Empatem CC-30 H is particularly suitable for lubricating the extraction from the mould of cast steel prepared in the crucible.

Properties

- Provides a good finish on the ingots.
- Low sulphur content, meaning that possible toxicity of machine operators is avoided, as is corrosion of the moulds.
- Low aromatics, thus reducing bothersome smoke.
- Good lubricating power for the requirements it is subject to.

Technical specifications

	UNIT	METHOD	VALUE
Appearance		Visual	Glossy and transparent
Colour		ASTM D 1500	3.5
Density at 15 °C	g/mL	ASTM D 4052	0.885
Viscosity at 40 °C	cSt	ASTM D 445	110
Viscosity at 100 °C	cSt	ASTM D 445	12
Viscosity index		ASTM D 2270	95
Flash point O/C	°C	ASTM D 92	240
Aniline point	°C	ASTM D 611	103
Pour point	°C	ASTM D 97	-9
Carbon Ramsbottom	%	ASTM D 524	0.1
Noack volatility, 1h at 150 °C		DIM 51581	0.50
Cu corrosion, 3h at 100 °C		ASTM D 130	1b

A safety data sheet is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. December 2008.